

NB1601-LWWtSc-G

Industrie-Router mit LTE + WLAN + BLE + 4x ETH + RS-232/485 + DIO + GNSS

Modularer Mobilfunk-Router mit 4-Port Ethernet Switch zur Vernetzung von schwer zugänglichen Orten.



Hauptmerkmale

Mobilfunk	1x LTE, UMTS, GSM
SIM	2x Micro SIM
WiFi / WLAN	1x Dual-band IEEE 802.11 a/b/g/n (Wi-Fi 4), 1x Bluetooth Low Energy
Ethernet	4x Fast Ethernet
IO	4x Digital I/O
Serielle / Feldbus	1x RS-232/485, 1x RS-232 Konsole
Ortung	Multi-GNSS
Betriebstemperatur	-40 °C bis +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates
Konformität	CE (RED), UKCA (RER), UL/IEC/EN 62368-1
Modularität	Erweiterungen auf Anfrage

Produktbeschreibung

Der NB1601 bietet die Schlüsseltechnologien für stationäre Anwendungen, die einen zuverlässigen Internetzugang benötigen.

Anwendungen

- Zustandsüberwachung
- Industrielle Sicherheit
- Fabrikautomation
- Remote Management
- Smart Buildings
- Mining
- Point of Sale
- Digital Signage

Spezifikation

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB (mit optionaler Software-Lizenz) FCC ID XPYTOBYL210
	Region Connectors SIM	Europe, Middle East and Africa (EMEA) 2x SMA female 2x Micro SIM - 3FF
WiFi / WLAN	Standard	1x Dual-band WLAN 2.4/5 GHz a/b/g/n (Wi-Fi 4) + BT 4.2 combo Wireless standard IEEE 802.11a/b/g/n (Wi-Fi 4) Bluetooth 4.2, Bluetooth Low Energy Frequency 2.4/5 GHz Antenna ports 2x2 MIMO Data rate (max) 144 Mbps 2.4 GHz 2x2 MIMO, 150 Mbps 5 GHz SISO Modes Client or access point (up to 10 clients) FCC ID Z64-WL18DBMOD
	Connector	2x SMA female
Ethernet	Standard	4x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	4x RJ45

Positioning	Standard	<p>1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -164 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream</p>
	Connector	1x SMA female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	<p>1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s 1x RS-232/485 combo (software switchable) Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115*200 Bit/s Protocol EIA-485 Signals A, B Signal level Differential output voltage, loaded 1.5 VDC - 3.6 VDC Bit rate Up to 115*200 Bit/s Termination 120 Ω for RS-485 configurable by software</p>
	Connector	2x Terminal block header 3.5 mm (screw locking)
IOs	Type	<p>2x Digital I/O Signals 1x DI, 1x DO DI signals +, - DI level Low: 0 - 3 VDC, high: 9 - 32 VDC DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO level 0 - 32 VDC/1A Isolation 1'500 VDC</p> <p>2x Digital I/O Signals 1x DI, 1x DO DI signals +, - DI level Low: 0 - 3 VDC, high: 9 - 32 VDC DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO level 0 - 32 VDC/1A Isolation 1'500 VDC Module COM-I/O shield</p>
	Connector	2x Terminal block header 3.5 mm (screw locking)
System	Core	600 MHz (HW Rev. A) or 1 GHz (HW Rev. B02) single core, 512 MB RAM, 4 GB flash
	Module Slots	1x miniPCIe / extension combo (USB), 1x Shield

Software	Features	<p>NetModule Router Software</p> <p>Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.</p> <p>General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog</p> <p>Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS</p> <p>Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)</p> <p>Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements</p> <p>Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,</p> <p>Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot</p> <p>Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN</p> <p>VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service</p> <p>Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports)</p> <p>Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)</p> <p>Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)</p> <p>Programmability SDK</p> <p>Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS/GPS</p> <p>Services Server with JSON-, NMEA stream</p>
Power	Input Voltage	<p>12, 24 VDC</p> <p>Nominal voltages 12, 24 VDC</p> <p>Absolute voltages 12 VDC to 24 VDC (-20 % / +20 %)</p>
	Connector	<p>1x Terminal block header 3.5 mm (screw locking)</p>
	Consumption	<p>7 W (average), 10 W (max)</p>
Mounting		DIN-Rail
Dimensions	W x H x D	Width 45 mm x height 124/134 mm x depth 110/121 mm
Weight		450 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40
MTBF		300'000 h / 34.2 years, according SN29500 at environmental temperature 40 °C
Lieferumfang		Device, General safety instructions, Terminal block
Certifications	Compliance	CE according to 2014/53/EU (RED); UKCA according to Radio Equipment Regulations 2017 No. 1206 (RER); UL/IEC/EN 62368-1; 2011/65/EU (RoHS)
	Domain	Industrial
Order Code		NB1601-LWWtSc-G