

# NB3800-3LWac-G

## Bahn-Router mit 3x LTE + WLAN-ac 5x ETH + GNSS + EN50155

Leistungstarker und modularer Mobilfunk-Router mit 5-Port Ethernet Switch für drahtlosen Internetzugang im Fahrzeug.



### Hauptmerkmale

|                           |   |
|---------------------------|---|
| <b>Mobilfunk</b>          | 3x LTE, UMTS, GSM   |
| <b>SIM</b>                | 4x Mini SIM   |
| <b>WiFi / WLAN</b>        | 1x Dual Band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients im Access Point Mode            |
| <b>Ethernet</b>           | 2x Gigabit Ethernet, 3x Fast Ethernet   |
| <b>Speisung</b>           | 24 VDC bis 48 VDC   |
| <b>Ortung</b>             | Multi-GNSS  |
| <b>Betriebstemperatur</b> | -40 °C bis +70 °C, EN 50155 class OT4/ST0   |
| <b>Software</b>           | Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates |
| <b>Konformität</b>        | CE (RED), Bahn (EN50155, EN45545), ITxPT optional   |
| <b>Modularität</b>        | Erweiterungen auf Anfrage   |

### Produktbeschreibung

Der leistungsstarke NB3800 ist mit seiner Ausstattung, seinen Bahnzulassungen und Schnittstellen zur Bordelektronik z.B. ideal für Passagier-WLAN, Fahrgastinformation, oder Videoüberwachung geeignet.

### Anwendungen

- Passagier-WLAN
- Passagier-Infotainment
- Fahrkartensysteme
- Videoüberwachung

### Spezifikation

|                          |                   |   |
|--------------------------|-------------------|---|
| <b>Mobile / Cellular</b> | <b>Standard</b>   | 3x Multimode LTE, UMTS, GSM for EMEA<br><b>4G - LTE</b> B1, B3, B7, B8, B20, B28A<br><b>3G - DC-HSPA+/UMTS</b> B1 (2100), B3 (1800), B8 (900)<br><b>2G - GSM/GPRS/EDGE</b> B3 (1800), B8 (900)<br><b>Category</b> LTE Cat 4<br><b>Antenna ports</b> 2x2 MIMO<br><b>Data rate down / up (max)</b> 150 Mbps / 50 Mbps<br><b>Voice</b> CSFB, VoLTE (mit optionaler Software-Lizenz)<br><b>FCC ID</b> - |
|                          | <b>Region</b>     | Europe, Middle East and Africa (EMEA)   |
|                          | <b>Connectors</b> | 6x TNC female   |
|                          | <b>SIM</b>        | 4x Mini SIM - 2FF   |
| <b>WiFi / WLAN</b>       | <b>Standard</b>   | 1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5)<br><b>Wireless standard</b> IEEE 802.11a/b/g/n/ac (Wi-Fi 5)<br><b>Frequency</b> 2.4/5 GHz<br><b>Diversity</b> 2x2 MIMO<br><b>Data rate (max)</b> 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz)<br><b>Modes</b> Client or access point (up to 100 clients)<br><b>FCC ID</b> TK4WLE600VX   |
|                          | <b>Connector</b>  | 2x TNC female   |
|                          | <b>Ethernet</b>   | 2x Gigabit Ethernet<br><b>Ethernet standard</b> 1000BASE-T, Auto MDIX<br><b>Speed</b> 10/100/1000 Mbps<br>3x Fast Ethernet<br><b>Ethernet standard</b> 100BASE-TX, Auto MDIX<br><b>Speed</b> 10/100 Mbps<br><b>Connector</b><br>2x M12 X-coded female, 3x M12 D-coded female  |

|                         |  |  |
|-------------------------|--|--|
| <b>Positioning</b>      | <b>Standard</b>                        | 1x Multi-GNSS<br><b>Receiver</b> BeiDou, Galileo, GLONASS, GPS<br>gpsOne Gen 9<br><b>Antennas</b> Active or passive<br><b>Tracking Sensitivity</b> Up to -160 dBm<br><b>Services</b> Standalone<br><b>CEP (Circular Error Probability)</b> < 2m (CEP 50), (Open sky conditions, Horizontal)  |
|                         | <b>Connector</b>                       | 1x TNC female  |
| <b>USB</b>              | <b>Standard</b>                        | 1x USB 2.0 Host  |
|                         | <b>Connector</b>                       | 1x Type A  |
| <b>Serial, Fieldbus</b> | <b>Protocol</b>                        | 1x RS-232<br><b>Protocol</b> EIA-232<br><b>Signals</b> TX, RX<br><b>Signal level</b> High > 5 VDC, low < -5 VDC<br><b>Bit rate</b> Up to 115 200 Bit/s   |
|                         | <b>Connector</b>                       | 1x M12 A-coded female  |
| <b>System</b>           | <b>Core</b>                            | 1.3 GHz dual core, 1 GB RAM, 4 GB flash  |
|                         | <b>Module Slots</b>                    | 2x miniPCIe (PCIe + USB), 4x miniPCIe (USB)  |
| <b>Software</b>         | <b>Features</b>                        | NetModule Router Software<br><b>Package</b> The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment.<br><b>General</b> Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog<br><b>Remote Management</b> Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS<br><b>Cellular Networking</b> Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license)<br><b>Wireless LAN</b> Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements<br><b>Link Management</b> Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision,<br><b>Services</b> DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SMTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot<br><b>Routing</b> Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN<br><b>VPN</b> OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service<br><b>Firewall</b> Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Address translation (based on SRC and DST ports)<br><b>Encryption</b> supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography)<br><b>Quality of Service</b> Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow)<br><b>Programmability</b> SDK<br><b>Troubleshooting</b> Logging, Ping, Traceroute, Tcpdump, Speed-test |
|                         | <b>Licenses</b>                        | GNSS/GPS<br><b>Services</b> Server with JSON-, NMEA stream   |
| <b>Power</b>            | <b>Input Voltage</b>                   | 24, 48 VDC<br><b>Nominal voltages</b> 24, 48 VDC<br><b>Absolute voltages</b> 24 VDC to 48 VDC (-30 % / +30 %)<br><b>Galvanic isolation</b> 1500 VDC<br><b>Standard</b> EN 50155 class S2/C1  |
|                         | <b>Connector</b><br><b>Consumption</b> | 1x M12 A-coded male<br>25 W (max)  |
| <b>Dimensions</b>       | <b>W x H x D</b>                       | Width 167/190 mm x height 121.1 mm x depth 106.5 mm  |
| <b>Weight</b>           |  | 1800 g   |
| <b>Environment</b>      | <b>Operating Temperature</b>           | -40°C to +70°C   |
|                         | <b>Ingress Protection Level</b>        | IP40   |
| <b>MTBF</b>             |  | 150'000 h / 17.1 years, according SN29500 at environmental temperature 40 °C   |

---

**Certifications****Compliance  
Domain**

CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT4/ST0, EN 45545  
Railway

---

**Order Code**

NB3800-3LWac-G