

NB3800-N-G

Railway Router with 1x 5G + 5x ETH + GNSS + EN50155

With excellent 5G mobile radio technology for wireless internet access in the vehicle incl. 5-port Ethernet switch.



Keyfeatures

Mobile / Cellular	1x 5G-NR, LTE-A Pro, UMTS
SIM	4x Mini SIM
Ethernet	2x Gigabit Ethernet, 3x Fast Ethernet
Power	24 VDC to 48 VDC
Positioning	Multi-GNSS
Temperature Range	-40 °C to +70 °C, EN 50155 class OT4/ST0
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED), Railway (EN50155, EN45545), ITxPT optional
Modularity	Extensions on request

Product description

The powerful NB3800 with its features, railway approvals and interfaces to on-board electronics, is ideal for applications like passenger WiFi, passenger information systems or video surveillance.

Applications

- Fleet Management
- Mining
- Passenger Infotainment
- Ticketing
- CCTV
- Telematics

Specifications

Mobile / Cellular	Standard	
		1x Multimode 5G-NR, LTE-A Pro, UMTS
		5G - NR n1, n2, n3, n5, n7, n8, n12*, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79
		2014/53/EU (RED): n1, n3, n7, n8, n20, n28, n38, n40, n77, n78
		4G - LTE-A Pro B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29DL, B30, B32, B34, B38, B39, B40, B41, B42, B43*, B46(LAA), B48(CRS), B66, B71
		2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40
		3G - DC-HSPA+/UMTS B1, B2, B3, B4, B5, B6, B8, B9, B19
		2014/53/EU (RED): B1 (2100), B3 (1800), B8 (900)
		5G NR Modes Sub-6 FDD and TDD
		LTE Category Cat. 20 up to 7CA
		MIMO 4x4 MIMO in 5G-NR support on n1, n2 n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79 and LTE B1, B2, B3, B4, B7, B25, B30, B38, B39, B40, B41, B42, B43, B46, B48, B66
		Antenna ports 4
		Power Class 23dBm (Power Class 3)
		Data rate down / up (max) up to 5.5 Gbps DL / 2.7 Gbps UL
		Operation Mode 5G Core SA and NSA operations
		3GPP 4G/5G Rel. 15, 3G HSPA+ Rel. 18
		FCC ID RI7FN980
		Voice -
		Region Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC)
		* future Module Firmware release
		Europe, Middle East and Africa (EMEA)
		4x TNC female
		4x Mini SIM - 2FF
	Region	
	Connectors	
	SIM	

Ethernet	Standard	2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps
	Connector	3x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps 2x M12 X-coded female, 3x M12 D-coded female
Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS gpsOne Gen 9 Antennas Active or passive Sensitivity Up to -161 dBm CEP (Circular Error Probability) <2m (Open sky conditions. Standalone) Min Update Rate 1Hz Services Standalone
	Connector	1x TNC female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	1x RS-232 Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s
	Connector	1x M12 A-coded female
System	Core	1.3 GHz dual-core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 4x miniPCIe (USB)
Software	Features	NetModule Router Software (supported features depending on product variant) Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNMP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDAP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test
	Licenses	GNSS Enabled service GNSS location service Server with JSON-, NMEA stream
Power	Input Voltage	24, 48 VDC Nominal voltages 24, 48 VDC Absolute voltages 24 VDC to 48 VDC (-30 % / +30 %) Galvanic isolation 1500 VDC Standard EN 50155 class S2/C1
	Connector Consumption	1x M12 A-coded male 25 W (max)
Dimensions	W x H x D	Width 167/190 mm x height 121.1 mm x depth 106.5 mm

Weight		1800 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40
MTBF		150'000 h / 17.1 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT4/ST0, EN 45545 Railway
Order Code		NB3800-N-G